

	Model No.	Capacity (S)		Reach (B1)		Weight kg	Measurements in mm							
		mm	Inch	mm	Inch		A	A1	A2	B	B2	B3	B4	L
Standard Duty	T186-600	600	(24)	60	(2 $\frac{3}{8}$)	3.4	30	12	76	32	44	30	76	710
	T186-900	900	(36)	60	(2 $\frac{3}{8}$)	4.4	30	12	76	32	44	30	76	1020
	T186-1500	1500	(60)	60	(2 $\frac{3}{8}$)	5.8	30	12	76	32	44	30	76	1625
	T186-2100	2100	(84)	60	(2 $\frac{3}{8}$)	7.6	30	12	76	32	44	30	76	2235
	T186-2400	2400	(96)	60	(2 $\frac{3}{8}$)	8.8	30	12	76	32	44	30	76	2540
Standard Duty Long Reach	T321-600	600	(24)	120	(4 $\frac{3}{4}$)	3.5	30	12	76	32	104	30	76	710
	T321-900	900	(36)	120	(4 $\frac{3}{4}$)	4.5	30	12	76	32	104	30	76	1020
	T321-1500	1500	(60)	120	(4 $\frac{3}{4}$)	5.9	30	12	76	32	104	30	76	1625
	T321-2100	2100	(84)	120	(4 $\frac{3}{4}$)	7.7	30	12	76	32	104	30	76	2235
	T321-2400	2400	(96)	120	(4 $\frac{3}{4}$)	8.9	30	12	76	32	104	30	76	2540
Medium Duty	T290-900	900	(36)	90	(3 $\frac{1}{2}$)	10.5	40	20	140	51	65	40	105	1070
	T290-1200	1200	(48)	90	(3 $\frac{1}{2}$)	12.1	40	20	140	51	65	40	105	1390
	T290-1500	1500	(60)	90	(3 $\frac{1}{2}$)	14.0	40	20	140	51	65	40	105	1690
	T290-2100	2100	(84)	90	(3 $\frac{1}{2}$)	18.0	40	20	140	51	65	40	105	2290
Medium Duty Long Reach	T285-900	900	(36)	200	(8)	11.5	40	20	140	51	180	40	105	1070
	T285-1200	1200	(48)	200	(8)	13.0	40	20	140	51	180	40	105	1390
	T285-1500	1500	(60)	200	(8)	15.0	40	20	140	51	180	40	105	1690
	T285-2100	2100	(84)	200	(8)	19.0	40	20	140	51	180	40	105	2290
Heavy Duty	T257-2100	2100	(84)	115	(4 $\frac{1}{2}$)	27.2	50	22	187	63.5	83	52	127	2335
	T257-2700	2700	(108)	115	(4 $\frac{1}{2}$)	32.0	50	22	187	63.5	83	52	127	2945